

XLPE  
 FRPVC (red stripe)  
 LHPVC (blue stripe)

F2CC...  
 ...001  
 ...002

Primary group code  
 Finish code

Copper 3 Core  
 600/1000V  
 SANS 1507

Size code	...naaa...	3915	3925	3004	3006	3010	3016
Conductor size	mm <sup>2</sup> nom	1.5	2.5	4	6	10	16
Conductor diameter	mm app.	1.6	2.0	2.5	3.0	4.0	5.0
Insulation diameter	mm app.	3.0	3.5	4.0	4.5	5.5	6.5
Cable diameter	mm app.	10.0	11.0	12.0	13.5	15.5	17.5
Cable mass	kg/m app.	0.18	0.22	0.29	0.37	0.53	0.74
Gross mass ( 500 m )	kg app.	105	130	165	190	285	360
Bending radius	mm min.	80	88	96	108	124	140
<b>Current rating</b>							
In ground	Amps	30	39	51	64	86	110
In air	Amps	25	33	45	57	79	105
<b>Resistance</b>							
dc @ 20°C	Ω/km max	12.10	7.41	4.61	3.08	1.83	1.15
ac @ 90°C	Ω/km max	15.43	9.45	5.88	3.93	2.33	1.47
<b>Reactance</b>							
Impedance	Ω/km	0.106	0.099	0.093	0.089	0.084	0.081
<b>Short circuit ratings</b>							
Symmetrical	kA (1sec)	0.2	0.3	0.5	0.8	1.4	2.2
Earth fault	kA (1sec)	1.2	1.3	1.5	1.6	1.9	2.1
(Three Phase) Volt Drop	mV/A/m	26.72	16.37	10.18	6.80	4.05	2.54

Last updated May 2006

When ordering please quote: primary + size + finish code  
 e.g. F2CC 3925 001



POWER BY INNOVATION... INNOVATION THROUGH PARTNERSHIPS

A member of the REUNERT Group

**CBI Electric African Cables**  
 PO Box 172, Vereeniging 1930 • Tel: +27 16 430 6000 • Fax: +27 16 423 6103  
 www.cbi-electric.com • afcab@cbi-electric.com

