

XLPE F2CC... Primary group code Copper 7 Core
 FRPVC SWA FRPVC (red stripe) ...111 Finish code 600/1000V
 LHPVC SWA LHPVC (blue stripe) ...212 SANS 1507

Size code	...naaa...	7910	7915	7925	7004	7006	7010	7016
Conductor size	mm ² nom	1	1.5	2.5	4	6	10	16
Conductor diameter	mm app.	1.3	1.6	2.0	2.5	3.0	4.0	5.0
Insulation diameter	mm app.	2.7	3.0	3.5	4.0	4.5	5.5	6.5
Bedding diameter	mm app.	10.0	11.0	12.0	13.5	15.0	18.5	21.5
Armour diameter	mm app.	12.5	13.5	14.5	16.0	17.5	21.5	24.5
Cable diameter	mm app.	15.5	16.5	17.5	19	21	25	28
Cable mass	kg/m app.	0.47	0.53	0.64	0.80	0.99	1.54	2.03
Gross mass (500 m)	kg app.	263	294	348	442	535	826	1074
Bending radius	mm min.	155	165	175	190	210	250	280
Resistance								
dc @ 20°C	Ω/km max	18.10	12.10	7.41	4.61	3.08	1.83	1.15
ac @ 90°C	Ω/km max	21.66	14.48	8.87	5.52	3.69	2.19	1.38
Reactance								
	Ω/km	0.112	0.106	0.099	0.093	0.089	0.084	0.081
Impedance								
	Ω/km	21.657	14.478	8.860	5.517	3.686	2.191	1.379
Short circuit ratings								
Symmetrical	kA (1sec)	0.14	0.21	0.33	0.54	0.80	1.35	2.15
Earth fault	kA (1sec)	1.15	1.24	1.37	1.56	1.74	2.70	3.08
(Three Phase) Volt Drop	mV/A/m	37.5	25.1	15.3	9.6	6.4	3.8	2.4

Last updated May 2006

When ordering please quote: primary + size + finish code

e.g. F2CC 7925 111



POWER BY INNOVATION... INNOVATION THROUGH PARTNERSHIPS

A member of the REUNERT Group

CBI Electric African Cables
 PO Box 172, Vereeniging 1930 • Tel: +27 16 430 6000 • Fax: +27 16 423 6103
 www.cbi-electric.com • afcab@cbi-electric.com

