

Only for use in applications protected from solar radiation.

XLPE F6CC... Primary group code
ZEROTOX SWA ZEROTOX (white stripe) ...313 Finish code

Copper 2 Core
600/1000V
SANS 1507


Size code	...naaa...	2915	2925	2004	2006	2010	2016	2025	2035	2050
Conductor size	mm ² nom	1.5	2.5	4	6	10	16	*25	*35	*50
Conductor diameter	mm app.	1.6	2.0	2.5	3.0	4.0	5.0	4.0	5.0	5.5
Insulation diameter	mm app.	3.0	3.5	4.0	4.5	5.5	6.5	6.0	7.0	7.5
Bedding diameter	mm app.	8.0	9.0	10.0	11.0	12.5	14.5	14.0	15.5	17.0
Armour diameter	mm app.	10.5	11.5	12.5	13.5	15.0	17.0	17.0	18.5	20.5
Cable diameter	mm app.	13.5	14.5	15.5	16.5	18.5	20.0	20.0	22.0	24.0
Cable mass	kg/m app.	0.43	0.48	0.56	0.65	0.82	1.03	1.11	1.34	1.64
Gross mass (500 m)	kg app.	226	256	302	347	441	551	579	690	880
Bending radius	mm min.	135	145	155	165	185	200	210	220	240
Current rating										
In ground	Amps	36	46	61	76	100	130	145	180	223
In air	Amps	30	40	53	68	92	120	131	160	195
Resistance										
dc @ 20°C	Ω/km max	12.10	7.41	4.61	3.08	1.83	1.15	0.73	0.52	0.39
ac @ 90°C	Ω/km max	15.43	9.45	5.88	3.93	2.33	1.47	0.93	0.67	0.49
Reactance										
Impedance	Ω/km	0.106	0.099	0.093	0.089	0.084	0.081	0.059	0.057	0.056
Zero sequence										
Resistance	Ω/km	22.06	16.50	12.36	10.05	8.17	6.66	5.53	4.99	4.31
Reactance	Ω/km	0.18	0.16	0.15	0.14	0.13	0.12	0.06	0.06	0.06
Short circuit ratings										
Symmetrical	kA (1sec)	0.2	0.3	0.5	0.8	1.4	2.2	3.2	4.4	6.4
Earth fault	kA (1sec)	1.2	1.3	1.4	1.5	1.7	2.0	2.4	2.5	3.0
(Single Phase) Volt Drop	mV/A/m	30.86	18.90	11.76	7.86	4.67	2.94	1.86	1.34	1.00

Last updated May 2006

*D Shaped Conductors.

When ordering please quote: primary + size + finish code

e.g. F6CC 2925 313



POWER BY INNOVATION... INNOVATION THROUGH PARTNERSHIPS

A member of the REUNERT Group

CBI Electric African Cables

PO Box 172, Vereeniging 1930 • Tel: +27 16 430 6000 • Fax: +27 16 423 6103

www.cbi-electric.com • afcab@cbi-electric.com

